Stampede

Heavy Duty, Low Odor Stripper



Description

STAMPEDE is an economical aggressive floor finish stripper with heavy-duty stripping action powerful enough to virtually drive finish right off the floor. It is formulated with a high performance blend of non-butyl solvents and an odorless ammonia substitute. The result is effective cutting action in a dilution that requires less product usage. When STAMPEDE is used, the only thing left is a bare floor ready to be coated.

Features and Benefits

Due to an effective blend of non-butyl solvents, powerful builders, wetting agents and an odorless ammonia substitute Stampede is able to penetrate and loosen multiple coats of finish for easy removal. At the same time, extended dilution ratios as high as 1:16 (8 oz/gallon) provide excellent value. Powerful, pleasant to work with and economical - STAMPEDE makes selecting the right stripper for your floor maintenance program a cinch.

STAMPEDE is recommended for use on terrazzo, vinyl composition, vinyl and various mineral tile floors.

Directions

- 1. For heavier build-ups, dilute 1:8 cool water. For light to medium build-up, use 1 part Stampede to 16 parts water.
- 2. Apply to a manageable area. Caution: treated areas may become slippery.
- 3. Allow solution to react for 5 to 10 minutes DO NOT ALLOW SOLUTION TO DRY ON FLOOR. Scrub with a floor machine or autoscrubber equipped with stripping pads. Doodle Bug around edges, etc.
- 4. Pick up spent solution with wet/dry vacuum or automatic scrubber. Rinse with plain water or 1 oz./gal. "BACK TO 7" as a rinse aid.

Warning: Not for use on linoleum, asphalt tile or rubber tile floors. Wear water repellant/slip resistant footwear. Wear rubber gloves and safety eyewear to prevent skin/eye contact when using by hand.

Learn More.....at www.multi-clean.com

- Training materials: Multi-Clean Method Bulletin 1406 provides detailed floor care procedures.
- Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bullelin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road Shoreview, Minnesota Phone 651-481-1900 Fax 651-481-9987 Web www.multi-clean.com



Warning: Not for use on linoleum, asphalt tile or rubber tile floors. Wear water repellant/slip resistant footwear. Wear rubber gloves to prevent skin contact when using by hand.

Properties

AppearancepH	•
Specific Gravity	
Flashpoint	
Dilution	
	1:8 Heavy stripping
Foam	Low - Moderate
Hardwater Tolerance	Very good
Ammonia	None
Butyl (2-butyl ethanol)	None
Phosphate	None
Storage Stability	Excellent
Freeze-Thaw Stability	Will freeze below 20°F. If frozen,
	thaw, stir and observe before use.

VOC compliance:

EPA, CA, IL, IN, MI, OH, OTC, UT, and Canadian regulations.

Packaging		
Size	Part No.	
55 gallon	906857	
5 BIB	906855	
1 gallon	906853	