


LANDA[®]
Kärcher Group

Industrial Pressure Washers
...Built Right to Do the Job Right

SLX-SLT

The Only Portable Hot Water Pressure Washer
that Delivers 200°F Cleaning at up to 9.8 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil



■ Extra-large **Heating Coil** made of cold-rolled, 3/4" Schedule 80 steel pipe with 5-year warranty; features **Stainless Steel Top Wrap**; unique lift-out design for easy and quick **Coil Access**.

■ Rugged 2" x 4" x 1/8" thick box steel frame, with compact footprint, shields key components; further protected by weather-resistant **Epoxy Powder Coat** finish; **Power Platform** is vibration isolated to minimize frame stress.

■ Water-resistant, recessed metal **Control Panel** has adjustable thermostat, combination hour meter and tachometer, volt meter, burner switch and tri-lingual operating instructions for added safety.

■ Industrial-duty **Tri-Plunger Pump** designed to run at low RPM for long life, 7-year warranty, with single-rail true-track **Pulley Adjustment**.

■ **Illustrated Warning Labels** universally understandable for liability protection.

■ 30-gallon diesel and 16-gallon gasoline **Fuel Tanks** (15-gallon diesel and 10-gallon gasoline on SLT) provide hours of uninterrupted operation; with elevated fuel lines to avoid suctioning of settled debris.

■ 50 ft. of double-wire braid **High Pressure Hose** rated for up to 6000 PSI and featuring a 24-inch safety hose guard for operator burst protection.

■ High-efficiency **Burner**, with adjustable numbered dial-in air flow has a **Fuel-Water Separator** for fuel pump protection.



■ Many **Safety Features**, including a rupture disk, thermal pump protector, flow switch, unloader valve, and safety lock on the trigger gun.

■ Corrosion-resistant **Float Tank** (field installed kit) has stainless steel inlet filter and 3/4" float valve with anti-siphon backflow protection; also allows for introduction of detergents in high-pressure mode.

■ Insulated, fatigue-free **Trigger Gun**, with swivel crimp fitting for a tangle-free hose. Stainless steel, dual-lance **Variable Pressure Wand** features an ergonomic design and easy adjusting of the water pressure while cleaning.

■ Efficient **2,900-Watt Generator** produces reliable power for burner.

SLT8-32624E

www.landa.com

WHY CHOOSE THE SLX or SLT

When it comes to heavy-duty grease or grime, most high-volume, hot water pressure washers fall short with their 150°F water. Our SLX, and smaller SLT, are the first pressure washers ever designed to deliver a high-volume flow at 200°F, hot enough to melt the toughest of oily messes. The SLX delivers enough hot water flow—up to 9.8 GPM—that you can operate two spray guns at the same time!



QUALITY: Packed with quality throughout, the SLX and SLT feature a top-of-the-line, belt-drive pump with 7-year warranty and low RPM for extended life, as well as a giant Schedule 80 heating coil, made of up to 300 ft. of 3/4-inch steel pipe with 5-year warranty.

DURABILITY: Extraordinarily rugged frame is made of 2-by-4-inch box steel with an all-metal power platform cushioned by 10 vibration isolators to minimize frame stress.

EFFICIENT: The SLX-SLT is heated by our high-efficiency SureFire or a Beckett burner with adjustable numbered dial-in air flow. The 3/4" heating coil is amazingly efficient due to its unique "breathing" design so it heats quieter while promoting optimum heat exchange.

FUNCTIONAL: The SLX-SLT has a remarkably compact footprint, is certified to UL-1776 safety standards, has six forklift guides for portability, and the recessed control panel is ideally positioned for curb access when the unit is mounted on a trailer or truck bed.

Model #	Part #	GPM	PSI	Pump RPM	Engine	CCs	Engine Fuel	Ship Wt (lbs)
SLX10-25324E	1.110-525.0	9.5	2500	1560	Honda GX660	688	Gasoline	2020
SLX10-32624E	1.110-067.0	9.8	2800	1640	Kubota D1105	1123	Diesel	2120
SLT6-32324E	1.110-520.0	5.9	3200	1570	Honda GX630	688	Gasoline	1245
SLT8-30324E	1.110-522.0	7.8	3000	1470	Honda GX660	688	Gasoline	1230
SLT6-32624E	1.110-065.0	6.25	3200	1625	Kubota D1105	1123	Diesel	1745
SLT8-32624E	1.110-066.0	8.0	3200	1450	Kubota D1105	1123	Diesel	1811

E = Electric start engine (battery not included)

Field Installed Options & Accessories

- 8.920-751.0 Float Tank w/ Inlet Injection
- 8.904-456.0 Downstream Injector
- 8.920-977.0 Steam Valve

Distributed by: